

fcREQUEST FOR INFORMATION

Date: January 27, 2025

Trisect Project No: TC24-114

Project Name: York Region Admin., Package D Renovation

CONSULTANTS RFI NO: TC24-114-24-X

To: Stephanie Kamburis @ G. Bruce Stratton Architects	REFERENCE: Washroom Revisions due to Space Limitations		
cc: Victor Chau @ York Region	Spec. Section:		
cc: Natalie Freitas @ York Region	Drawing No.(s): Various Attachments: Photos		
From: Tom Butkovic, Ivan Lulic, Jay Cowie			
Interior Design ☐ Architectural ☐ Struct	ural Mechanical Electrical		
RESPONSE/INFORMATION REQUIRED BY: Jan. 31, 2025			
<u>-</u>	·		

On behalf of the mechanical subcontractor, please review and reply to the following RFI:



Request For Information 24-277-010

Jan 27, 2025

Project Name Project Address

YORK REGION VARIOUS PROJECTS 17250 Young Street Newmarket, ON

To From

Name Name

Tom Butkovic INZAMAN KHAN

Company

TRISECT CONSTRUCTION Consult Mechanical Inc.

Email Email

tbutkovic@trisectconstruction.com inzaman@consultmechanical.com

Address

4020A SLADEVIEW CRESCENT, UNIT 7 MISSISSAUGA,

ON L5L 6B1 JOB: 1300 INSLINGTON SUITE 103

54 Audia Court, Unit 2 Concord, ON L4K 3N5

Title SCHEDULE IMPACT COST IMPACT

Washroom revision due to space limitations Probable Probable

RETURN BY Jan 31, 2025

Information Requested

Please refer to the below 3 options and advise:

- 1. Re-works of the piping services in the chase impeding the new design.
- 2. Reorientations of the layout by switching the WC and urinal placement
- 3. Possibility of a smaller WC carrier. See alternate option attached.

GPY response: Alternate WC carrier can be used as long as the alternate carrier is compatible with the specified water closet. Coordinate mounting height with the Architect.

Engineering Specification

Job Name	Contractor
Job Location	Approval
	Contractor's P.O. No.
	Representative

ISCA-121-BF

Industry Standard Vertical Carrier for Floor Mounted Back Outlet Bowl

Specification

Watts ISCA-121-BF *Industry Standard* vertical water closet carrier for floor mounted back outlet bowl, with epoxy coated cast iron fitting, 4"(102) no hub waste and 2"(51) no hub vent connections, epoxy coated cast iron foot supports and patented compression seal faceplate assembly, ABS nipple with integral test cap and neoprene bowl gasket, plated hardware and chrome cap nuts.

Call customer service if you need assistance with technical details.

Options		
Suffix	Description	
-CI	Cast Iron Nipple	
-HS	Hub & Spigot Connections	


NOTICE

Anchor legs to concrete floor with minimum 1/2"(13) anchor bolts (by others).

Dual slotted carrier feet require one 1/2"(13) anchor bolt per foot.

x = 5 3/4"(146) Maximum with Standard Nipple

2"(51) Vent 1 1/2" 6 1/2" 6 23/32" (170) 2 3/16"(56) 2 3/16"(56) 2 3/32"(53) 2 3/32"(53) 2 3/32"(53)



NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: T: (800) 338-2581 • Watts.com **Canada:** T: (888) 208-8927 • Watts.ca

Latin America: T: (52) 55-4122-0138 • Watts.com

ES-WD-ISCA-121-BF 2348 © 2023 Watts